



## LIGHTING-BOLLARD 200 LED

Stainless steel | 620 mm

### Specifications


Fixed mounting: Cylindrical stainless-steel lighting bollard as permanent fixtures. With satined or clear acryl glass. Reflective slats surround the light unit. With energy efficient LED technology. Internal cable plus electric ballast for connection to a 230 Volt (AC) power source. Protection type IP 54.

### Mounting

Screw-on (Fixed mounting)  
Removable with 3p-Technologie on request

### Finish

- Stainless steel 1.4301 pickled and smoothed, grain 240
- Stainless steel 1.4301 with powder coating in standard RAL colours or DB 703
- Available with satined or clear acryl glass
- Supplied with LED stick with 3 x 3 LEDs
- Lower fitting: hexagon shell safety screws with pin, incl. key



	Light unit	Acryl glass	Finish	Fixed mounting
<b>Lighting-Bollard 200 LED</b>	LED stick	clear	pickled/smoothed	<b>200.101</b>
<b>Lighting-Bollard 200 LED</b>	LED stick	satined	pickled/smoothed	<b>200.110</b>
<b>Lighting-Bollard 200 LED</b>	LED stick	clear	powder coating	<b>201.101</b>
<b>Lighting-Bollard 200 LED</b>	LED stick	satined	powder coating	<b>201.110</b>



LED, Stainless steel, clear acryl glass



### Technical information

#### (LED stick)

- Light unit: LED stick with 3 x 3 LEDs
- Connection voltage: 230 Volt AC
- Power: 9 Watt (incl. 11-Watt driver unit)
- Luminous flux: 1000 lm
- Max. power input: 350 mA
- Light colour: 3000 K (warm white)
- Protection class 1, protection type IP 54