

5/2-way valve, Single-sided electromagn. monost. G1/4, 230V,50Hz

5/2-way valve, Single-sided electromagnetic, monost. G1/4, 230V,50 Hz, Operating pre. 2.5 - 10 bar, Operating temp. -10°C to 60°C. This valve design, featuring the Tapered Tee Seal®, offers the ability to run without lubrication and supports almost any compressed air quality.The valves are largely resistant to dirt and can thus also be used under extreme conditions without any problems.Leakage is now a thing of the past and the spool no longer sticks, even after long idle periods.

4047322278560

Article number	**106594**
Type number	**517.425**
Your price:	**101,29 € / 1 Stk**

Productdata

Date:	**14/05/2018**
Price Unit:	1
Quantity Unit:	Stk
Sales Unit:	1
Quantity min:	1
Circuit diagram	35
Connection	G 1/4
DN	7.5
Electrical connection	Coupler plug PG 9, form B
Flow rate 1	1500 Nl/min
Flow rate measurement 1	Flow rate at 6 bar and Δp 1.0 bar
Function	5/2
Housing	Anodised aluminium, blue
Max. operating pressure	10 bar
Max. temperature range	60 °C
Min. operating pressure	2.5 bar
Min. pilot pressure	2.5 bar
Min. temperature range	-10 °C
Operation	Monostable

Page No.	HK322
Protection IP	IP 65 (DIN 46244)
Sealant	NBR
Spool	Stainless steel
Voltage	230 V AC, 50 Hz

Telephone: +49 (0) 7125 94 97-0
Email : info@riegler.de

Subject technical changes

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach