

5/2-way valve, Pneumatic, »4A«, bistable, G 1/2

5/2-way valve, Pneumatic, »4A«, bistable, G 1/2, Operating pressure 1.5 - 8 bar, Temperature range max. 70 °C. 5/2-way pilot valves - Pneumatic -

4047322309684

Article number	**116065**
Type number	**516.5006**
Your price:	**79,73 € / Stk**

Scale of prices:

amount	Price	Unit
1	79,73 €	1 Stk

Productdata

Date:	**23/09/2019**
Price Unit:	1
Quantity Unit:	Stk
Content:	1 Stk
Quantity min:	1
Connection	G 1/2
Control air port	G 1/8
Exhaust connection	G 1/2
Flow rate [l/min]	2000
Flow rate measurement	At P<subscript>1</subscript> = 8 bar, P<subscript>2</subscript> = 6 bar and pressure drop Δ<subscript>p</subscript> = 1 bar
Function	5/2
Max. operating pressure [bar]	8
Max. temperature range [°C]	70
Min. operating pressure [bar]	1.5
Operation	Bistable
Page No.	HK464
Size	400
Symbol	28

Telephone: +49 7125 9497-8320
Email : info@riegler.de

Subject technical changes

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach

Valve body	Aluminium alloy