

Service unit 2-part »Standard«, Protective cage, Size 4, G 1

Service unit 2-part »Standard«, PC container, protective cage, Size 4, G 1, Input pressure max. 16 bar, Control range 0.5 - 10 bar. Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

4047322121910

Article number	**101057**
Type number	**866 S**
Your price:	**415,98 € / Stk**

Scale of prices:

amount	Price	Unit
1	415,98 €	1 Stk

Productdata

Date:	**23/09/2019**
Price Unit:	1
Quantity Unit:	Stk
Content:	1 Stk
Quantity min:	1
A [mm]	220
B [mm]	452
Bowl	Polycarbonate container with protective cage
C [mm]	190.6
Condensate drain	Semi-automatic
DN	25
Filter rating [µm]	40
Flow rate [l/min]	4000
Flow rate measurement	At P₁= 8 bar, P₂ = 6 bar and pressure drop Δ_p = 1 bar
Housing	Die-cast zinc / aluminium, painted silver
Max. ambient temperature [°C]	60

Telephone: +49 7125 9497-8320
Email : info@riegler.de

Subject technical changes

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach

Max. control range [bar]	10
Max. input pressure [bar]	16
Max. medium temperature [°C]	60
Min. control range [bar]	0.5
Page No.	HK130
Pressure gauge display max. [bar]	16
Pressure gauge display min. [bar]	0
Pressure gauge Ø [mm]	63
Sealant	NBR
Series	Standard
Sight dome	PA
Size	4
Thread	G 1