




Throttle check valve, Discharge throttle (»C«) push-in connector

Throttle check valve, Discharge throttle (»C«) push-in connector hose 10, G 1/4, PN max. 10 bar, Temperature 0 °C to 70 °C. For fine regulation of a cylinder piston speed and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder. Compact type of construction, also ideal where space is restricted. On the version with a knurled screw, the set volumetric flow rate can be locked with the hexagon nut to obtain a fixed setting.



4047322180948

Article number	106963
Type number	340.014-10
Your price:	13,75 € / Stk

Scale of prices:

amount	Price	Unit
1	13,75 €	1 Stk

Productdata

Date:	23/09/2019
Price Unit:	1
Quantity Unit:	Stk
Content:	1 Stk
Quantity min:	1
Adjusting screw	Nickel-plated brass
B [mm]	51.4
C [mm]	26.8
Captive seals	Polyamide (glass fibre-reinforced)
For hose [mm]	10
Hollow bolt	Nickel-plated brass
Internal parts	Brass with a bare metal surface
Max. operating pressure [bar]	10
Max. temperature range [°C]	70
Min. temperature range [°C]	0

Page No.	HK501
Pivoting arm	Nickel-plated brass
Sealant	NBR
Thread	G 1/4
a/f [mm]	17