




Throttle valve, Both sides throttling (»B«) quick connector

Throttle valve, Both sides throttling (»B«) quick connector Hose 10/8, G 3/8, PN max. 10 bar, Temperature 0 °C to 70 °C. For regulation of a cylinder piston speed at both ends and control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece for mounting directly. Compact type of construction, also ideal where space is restricted.



4047322181150

Article number	106978
Type number	359.038-10
Your price:	16,89 € / Stk

Scale of prices:

amount	Price	Unit
1	16,89 €	1 Stk

Productdata

Date:	23/09/2019
Price Unit:	1
Quantity Unit:	Stk
Content:	1 Stk
Quantity min:	1
Adjusting screw	Nickel-plated brass
B [mm]	50
C [mm]	30.5
Captive seals	Polyamide (glass fibre-reinforced)
For hose [mm]	10 / 8
Hollow bolt	Nickel-plated brass
Internal parts	Brass with a bare metal surface
Max. operating pressure [bar]	10
Max. temperature range [°C]	70
Min. temperature range [°C]	0
Page No.	HK502
Pivoting arm	Nickel-plated brass

Sealant	NBR
Thread	G 3/8
a/f [mm]	20