



Mobile platform stair (Light metal)

- + Mobile platform stair made of sturdy aluminium profiles
- + Work inclination: 45°
- + Step width: 600 – 800 – 1000 mm
- + Aluminium corrugated, depth of steps 225 mm for extra safe ascendency and a maximum of comfort
- + Platform extensions in width or length are available on request
- + Can easily be manouvered due to the 2 castors (Ø 125 mm) at the supporting part
- + Aluminium grating or aluminium perforated surfaces are available on request
- + Supplied in pre-assembled modules



i According to DIN EN ISO 14122-3 (regarding "Access to machineries") all platforms with a height of 0.50 m or higher have to be equipped with a railing.

Number of steps			2	3	4	5	
1		A up to approx.	in m	2.40	2.60	2.80	3.00
2		B approx.	in m	0.40	0.60	0.80	1.00
Projection approx.			in m	1.16	1.36	1.56	1.76
Type of step			Aluminium corrugated				
Article No. (Step width 600 mm)			810335	810342	810359	810366	
Article No. (Step width 800 mm)			810373	810380	810397	810403	
Article No. (Step width 1000 mm)			810410	810427	810434	810441	
Article No. (1 hand rail and railing)			818508	818515	818522	818539	
Depth of steps mm			600	800	1000		
Article No. Platform extension, aluminium, per 225 mm			818607	818614	818621		
Article No. Front railing			818638	818645	818652		
Article No. Steps with steel grated			818546	818553	818560		
Article No. Steel perforated			818577	818584	818591		
Article No. Rail extension, per 225 mm						818669	