



### Throttle check valve, Discharge throttle (»C«) quick connector

Throttle check valve, Discharge throttle (»C«) quick connector Hose 10/8, G 3/8, PN max. 10 bar, Temperature 0 °C to 70 °C. For fine regulation of a cylinder piston speed and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder. Compact type of construction, also ideal where space is restricted.



4047322181013

Article number	<b>106933</b>
Type number	<b>358.038-10</b>
Your price:	<b>16,89 € / Stk</b>

#### Scale of prices:

amount	Price	Unit
1	16,89 €	1 Stk

### Productdata

Date:	<b>23/09/2019</b>
Price Unit:	1
Quantity Unit:	Stk
Content:	1 Stk
Quantity min:	1
Adjusting screw	Nickel-plated brass
B [mm]	50
C [mm]	30.5
Captive seals	Polyamide (glass fibre-reinforced)
For hose [mm]	10 / 8
Hollow bolt	Nickel-plated brass
Internal parts	Brass with a bare metal surface
Max. operating pressure [bar]	10
Max. temperature range [°C]	70
Min. temperature range [°C]	0
Page No.	HK500

Pivoting arm	Nickel-plated brass
Sealant	NBR
Thread	G 3/8
a/f [mm]	20