

Flowcooler with air-cooled cooling machine and closed evaporator, for the cooling of circulators connected in series, housing of stainless steel with handle. The refrigerating unit works continuously.

### Technical data according to DIN 12876

Operating temperature range	-30...50 °C
Safety classification	Class I / NFL
Cooling power	
at 15°C	0,6 kW
at 0°C	0,47 kW
at -20°C	0,12 kW
Refrigeration machine	air-cooled, natural refrigerant
Refrigerant	R290
Refrigerant quantity	0,08 kg
Gas warning sensor	without
Liquid connection	M16x1 male
Overall dimensions WxDxH **	280x340x465 mm
Net weight	30 kg
Power supply requirement	230V 1~ 50Hz
max. current	3 A
min. Fuse (1 phase)	10A
max. Fuse (1 phase)	16A
min. ambient temperature	5 °C
max. ambient temperature	40 °C



Order-No.: 3002.0001.99

**from Serial-No.:** 196692 1.0/14

Technical details and dimensions are subject to change. No liability is accepted for errors or omissions. Illustrations can deviate from the original.

Output data valid for: Room temperature 20° C  
in accordance with EN60034-1 the following voltage and frequency tolerances are valid:  
Voltage + / - 5% with a simultaneous frequency tolerance of + / - 2%  
Example -5% voltage and + 2% frequency -> not allowed!  
-5% voltage and - 2% frequency -> allowed

Information to Electromagnetic compatibility:  
Classification (disturbance) to EN55011: Class A, Group 1

\*\* Please respect space requirements. See operating conditions at [www.huber-online.com](http://www.huber-online.com)