

Electr. pressure transducer, 0-600 bar, G 1/2, CrNi steel 1.4571

Electr. pressure transducer, viscous, media containing solids, Non-linearity 0.2%, Meas. range 0-600 bar, G 1/2, CrNi steel 1.4571. Pressure transmitter in CrNi steel with flush diaphragm for measuring viscous, pasty, adhesive, crystallising, particle-laden or contaminated media, which would clog the pressure channel of conventional process connections. Applications: Electronic pressure measurement in the food and beverages sector, hydraulic power units or industrial applications in general.

4047322379427

Article number	**102723**
Type number	**896.600**
Your price:	**523,35 € / Stk**

Scale of prices:

amount	Price	Unit
1	523,35 €	1 Stk

Productdata

Date:	**23/09/2019**
Price Unit:	1
Quantity Unit:	Stk
Content:	1 Stk
Quantity min:	1
Electrical connection	With right-angle connector acc. to DIN EN 175301-803 A
Housing	CrNi steel 1.4571
Max. ambient temperature [°C]	80
Max. medium temperature [°C]	70
Measuring range max. bar	600
Measuring range min. bar	0
Min. ambient temperature [°C]	-20
Min. medium temperature [°C]	-30
Nonlinearity	0.2% of span
Operating voltage	DC 10 (14) ... 30 V

Telephone: +49 7125 9497-8320
Email : info@riegler.de

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach

Subject technical changes

Output signal	4 - 20 mA, 2-wire
Page No.	HK233
Protection IP	IP 65 acc. to EN 60529
Thread	G 1/2
Type	S-11
Wetted parts	CrNi steel 1.4571

Telephone: +49 7125 9497-8320
Email : info@riegler.de

Subject technical changes

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach