

Precision filter regulator, Free of non-ferrous metals, 0.2-5 bar

Precision filter regulator without pressure gauge, Free of non-ferrous metals, G 1/4, Control range 0.2 - 5 bar. Diaphragm pressure regulators containing no non-ferrous metals, with secondary venting, combined with a centrifugal separator for applications requiring an extremely accurate working pressure.

4047322118392

Article number	**101219**
Type number	**778.85**
Your price:	**78,09 € / Stk**

Scale of prices:

amount	Price	Unit
1	78,09 €	1 Stk

Productdata

Date:	**23/09/2019**
Price Unit:	1
Quantity Unit:	Stk
Content:	1 Stk
Quantity min:	1
A [mm]	60
B [mm]	216
C [mm]	120
D [mm]	96
Filter rating [µm]	10
Flow rate	750 l/min
Gauge port size	G 1/4
Housing	Die-cast zinc
Max. ambient temperature [°C]	60
Max. control range [bar]	5
Max. input pressure [bar]	16
Max. internal air consumption	0.2 l/min, depending on input pressure and control range

Telephone: +49 7125 9497-8320
Email : info@riegler.de

Subject technical changes

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach

Max. medium temperature [°C]	60
Medium	Micro-filtered, unoiled compressed air (0.01 µm)
Min. control range [bar]	0.2
Page No.	HK155
Sealant	NBR
Thread	G 1/4