

Flowcooler with air-cooled cooling machine and closed evaporator, for the cooling of circulators connected in series, housing of stainless steel with handle. The refrigerating unit works continuously.

Technical data according to DIN 12876

Operating temperature range	-30...50 °C	
Safety classification	Class I / NFL	
Cooling power		Order-No.: 3001.0001.99
at 15°C	0,4 kW	
at 0°C	0,35 kW	
at -20°C	0,1 kW	
Refrigeration machine	air-cooled, natural refrigerant	
Refrigerant	R290	
Refrigerant quantity	0,06 kg	
Gas warning sensor	without	
Liquid connection	M16x1 male	
Overall dimensions WxDxH **	250x310x415 mm	
Net weight	23 kg	
Power supply requirement	230V 1~ 50/60Hz	
max. current	2,7 A	
min. Fuse (1 phase)	10A	
max. Fuse (1 phase)	16A	
min. ambient temperature	5 °C	
max. ambient temperature	40 °C	

from Serial-No.: 171863 **1.0/12**

Technical details and dimensions are subject to change. No liability is accepted for errors or omissions. Illustrations can deviate from the original.

Output data valid for: Room temperature 20° C
in accordance with EN60034-1 the following voltage and frequency tolerances are valid:
Voltage + / - 5% with a simultaneous frequency tolerance of + / - 2%
Example -5% voltage and + 2% frequency -> not allowed!
-5% voltage and - 2% frequency -> allowed

Information to Electromagnetic compatibility:
Classification (disturbance) to EN55011: Class A, Group 1

** Please respect space requirements. See operating conditions at www.huber-online.com