

Chiller with air-cooled refrigerating unit and circulation pump. Evaporator (cooler), tank and housing of stainless steel. Pump made of industrial plastic material. Temperature adjustment and temperature display digital. Level indicator with sight glass.

NEW: OLÉ controller:

OLÉ combines state-of-the-art technology with simple operation. Models with OLÉ controller are suitable for routine tasks in research and industry and are convincing as practice oriented basic equipment:

- * Large, bright OLED display
- * Simple operation with menu navigation
- * Simultaneous display of set point, internal temperature, Tmin and Tmax
- * USB (Device) and RS232 interfaces
- * Autostart function for power failure

Option: Pt100 sensor connection #10519 to display (not control) e.g. of the process temperature (only available factory fitted, additional charge)

3-2-2 warranty - registration required.

Technical data according to DIN 12876

| | |
|---------------------------------|--------------------------------|
| Operating temperature range | -20...40 °C |
| temperature set point / display | digital |
| Internal temperature sensor | Pt100 |
| Resolution of display | 0,1 K |
| Temperature stability at -10°C | 0,5 K |
| Alarm message | optic, acoustic |
| Safety classification | Class I / NFL |
| Cooling power | |
| at 15°C | 1 kW |
| at 0°C | 0,8 kW |
| at -10°C | 0,5 kW |
| at -20°C | 0,15 kW |
| Refrigeration machine | air-cooled, CFC- and HCFC-free |
| Refrigerant | R507 |
| Refrigerant quantity | 0,3 kg |
| Circulation pump | B |
| at 0,5 bar | 21 l/min |
| max. delivery | 29 l/min |
| max. delivery pressure | 1,0 bar |
| Pump connection | G3/4 male |
| min. filling capacity | 3,8 l |
| Expansionsgefäß | 1,7 l |
| Overall dimensions WxDxH ** | 350x496x622 mm |
| Net weight | 49 kg |
| Power supply requirement | 230V 1~ 50/60Hz |
| max. current | 6 A |
| min. Fuse (1 phase) | 10A |
| max. Fuse (1 phase) | 16A |
| Degree of Protection | IP20 |
| min. ambient temperature | 5 °C |
| max. ambient temperature | 40 °C |



Order-No.: 3012.0124.98

from Serial-No.: 258716

1.0/17

Technical details and dimensions are subject to change. No liability is accepted for errors or omissions. Illustrations can deviate from the original.

Included Accessories:

cover expansion vessel #25178, hose coupling for G3/4 male,

Optional accessories:

drain valve #6839, temperature control / - connection hoses, thermofluids, further accessories, etc.: see catalog.

Technical data according to DIN 12876

Output data valid for: Room temperature 20°C

in accordance with EN60034-1 the following voltage and frequency tolerances are valid:

Voltage + / - 5% with a simultaneous frequency tolerance of + / - 2%

Example -5% voltage and + 2% frequency -> not allowed!

-5% voltage and - 2% frequency -> allowed

Information to Electromagnetic compatibility:

Classification (disturbance) to EN55011: Class A, Group 1

Special Case: Acetone and Polyglycol: The plastic pump is not resistant against acetone and polyglycols (depending on the manufacturer). It is recommended that water is mixed with either glysantine or ethylene glycol for freeze protection. A more resistant plastic is available on request at an additional cost.

** Please respect space requirements. See operating conditions at www.huber-online.com