

Flowcooler with air-cooled cooling machine and closed evaporator, for the cooling of circulators connected in series, housing of stainless steel with handle. The refrigerating unit works continuously.

Technical data according to DIN 12876

Operating temperature range	-30...50 °C
Safety classification	Class I / NFL
Cooling power	
at 15°C	0,2 kW
at 0°C	0,15 kW
at -20°C	0,07 kW
Refrigeration machine	air-cooled, natural refrigerant
Refrigerant	R290
Refrigerant quantity	0,05 kg
Gas warning sensor	without
Liquid connection	M16x1 male
Overall dimensions WxDxH **	190x250x360 mm
Net weight	16 kg
Power supply requirement	230V 1~ 50Hz
max. current	1,4 A
Fuse (1 phase)	2 A
min. Fuse (1 phase)	10A
max. Fuse (1 phase)	16A
min. ambient temperature	5 °C
max. ambient temperature	40 °C



Order-No.: 3000.0001.99

from Serial-No.:

105104

1.2/09

Technical details and dimensions are subject to change. No liability is accepted for errors or omissions. Illustrations can deviate from the original.

Output data valid for: Room temperature 20° C
 in accordance with EN60034-1 the following voltage and frequency tolerances are valid:
 Voltage + / - 5% with a simultaneous frequency tolerance of + / - 2%
 Example -5% voltage and + 2% frequency -> not allowed!
 -5% voltage and - 2% frequency -> allowed

Information to Electromagnetic compatibility:
 Classification (disturbance) to EN55011: Class A, Group 1

** Please respect space requirements. See operating conditions at www.huber-online.com