




Throttle check valve, Discharge throttle (»C«) quick connector

Throttle check valve, Discharge throttle (»C«) quick connector Hose 10/8, G 1/4, PN max. 10 bar, Temperature 0 °C to 70 °C. For fine regulation of a cylinder piston speed and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder. Compact type of construction, also ideal where space is restricted. On the version with a knurled screw, the set volumetric flow rate can be locked with the hexagon nut to obtain a fixed setting.



4047322180320

Article number	106955
Type number	333.014-10
Your price:	12,35 € / 1 Stk

Productdata

Date:	14/05/2018
Price Unit:	1
Quantity Unit:	Stk
Sales Unit:	1
Quantity min:	1
Adjusting screw	Nickel-plated brass
B	51.4 mm
C	28.5 mm
Captive seals	Polyamide (glass fibre-reinforced)
For hose	10 / 8 mm
Hollow bolt	Nickel-plated brass
Internal parts	Brass with a bare metal surface
Max. operating pressure	10 bar
Max. temperature range	70 °C
Min. temperature range	0 °C
Page No.	HK347
Pivoting arm	Nickel-plated brass
Sealant	NBR
Thread	G 1/4

a/f

17 mm