




2/2-way toggle lever valve, both sides, Quick connector, G 1/8

2/2-way toggle lever valve, both sides, Quick connector for hose G 1/8 IT, G 1/8, PN max. 8 bar, Temperature 0 °C to 70 °C. Manually operated toggle valves, 2/2 and 3/2-way types. For all applications where compressed air must be switched on or off quickly and easily or a cylinder operated manually. Designed as a banjo-type valve with a hollow bolt and ring piece. Suitable for screwing directly into the equipment or for panel mounting. Compact type of construction, also ideal where space is restricted.



4047322181204

Article number	107009
Type number	360.018-1/8
Your price:	23,94 € / 1 Stk

Productdata

Date:	14/05/2018
Price Unit:	1
Quantity Unit:	Stk
Sales Unit:	1
Quantity min:	1
B	55 mm
C	16 mm
Captive seals	Polyamide (glass fibre-reinforced)
For hose	G 1/8 female thread mm
Hollow bolt	Nickel-plated brass
Internal parts	Brass with a bare metal surface
Max. operating pressure	8 bar
Max. temperature range	70 °C
Min. temperature range	0 °C
Page No.	HK350
Pivoting arm	Nickel-plated brass
Sealant	NBR
Thread	G 1/8
Thread for panel mounting	M12x0.75 (max. plate thickness 4 mm)

Toggle	Nickel-plated brass
Version	2/2-way
a/f	14 mm