

Service unit »ONE« without pressure switch, G 1/2

Service unit »ONE« without pressure switch, G 1/2, Input pressure max. 10 bar, Control range 0.5 - 8 bar, Temp. -10 °C to 50 °C. Multifunctional service unit with 6 functions in a single device:3/2-way valve (manually operated), filter with automatic drain valve, air ports, pressure regulator, pressure gauge, soft start valveThis combination of extremely good flow rates and a wide range of functions integrated in a single, compact unit saves valuable space and is unmatched by any similar product available in the market!Soft starting independently of the load and easy replacement of the filter cartridge under pressure are just two of the other outstanding features of this amazing device.

4047322284806

Article number	**101124**
Type number	**533.303**
Your price:	**268,81 € / 1 Stk**

Productdata

Date:	**14/05/2018**
Price Unit:	1
Quantity Unit:	Stk
Sales Unit:	1
Quantity min:	1
A	165.5 mm
B	144 mm
C	35 mm
Filter rating	20 µm
Flow rate	4000 l/min
Flow rate measurement	At P2 = 6.3 bar and pressure drop Δp = 1 bar
Max. control range	8 bar
Max. input pressure	10 bar
Max. temperature range	50 °C
Medium	Pneumatics
Min. control range	0.5 bar
Min. temperature range	-10 °C

Telephone: +49 (0) 7125 94 97-0
Email : info@riegler.de

Subject technical changes

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach

Operating voltage	24 V DC (for valves and pressure switch)
Page No.	HK095
Protection IP	IP 65
Series	ONE
Thread	G 1/2