




Valve disc HDM Connection 6 mm 5/2-way monostable, only use 1 pin

Valve disc for valve terminal HDM, Connect. 6 mm, 5/2-way, monostable (only uses one PIN, Source 2 signals). These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors. Suitable for filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous. Monostable (non-latching) version of manual control also available on request. The operating pressure is based on the installed input plates.



4047322286688

Article number	106685
Type number	F 6
Your price:	99,99 € / Stk

Scale of prices:

amount	Price	Unit
1	99,99 €	1 Stk

Productdata

Date:	23/09/2019
Price Unit:	1
Quantity Unit:	Stk
Content:	1 Stk
Quantity min:	1
Flow rate [NI/min]	500
Function	5/2-way, monostable (uses only one pin, two signals assigned)
Manual control	latching
Max. temperature range [°C]	60
Min. temperature range [°C]	-10
Page No.	HK483
Piloting	Max. 16 (e.g. 16 spring return valves)

Power input	0.6 W per pilot
Protection IP	IP 65