

## Service unit 3-part »Standard« with PC container, Size 4, G 1 1/2

Service unit 3-part »Standard« with polycarbonate container, Size 4, G 1 1/2, Input pressure max. 16 bar, Control range 0.5-10 bar. Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

4047322121675

| | |
|---|---|
| Article number | **101071** |
| Type number | **850 H** |
| Your price: | **694,68 € / Stk** |

### Scale of prices:

| amount | Price | Unit |
|---|---|---|
| 1 | 694,68 € | 1 Stk |

# Productdata

| | |
|---|---|
| Date: | **23/09/2019** |
| Price Unit: | 1 |
| Quantity Unit: | Stk |
| Content: | 1 Stk |
| Quantity min: | 1 |
| A [mm] | 395 |
| B [mm] | 313.4 |
| Bowl | Polycarbonate container |
| C [mm] | 70 |
| Condensate drain | Semi-automatic |
| DN | 35 |
| Filter rating [µm] | 40 |
| Flow rate [l/min] | 5000 |
| Flow rate measurement | At P<sub>1</sub> = 8 bar, P<sub>2</sub> = 6 bar and pressure drop Δ<sub>p</sub> = 1 bar |
| Housing | Die-cast zinc / aluminium, painted silver |
| Max. ambient temperature [°C] | 60 |

Telephone: +49 7125 9497-8320
Email : info@riegler.de

Subject technical changes

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach

| | |
|---|---|
| Max. control range [bar] | 10 |
| Max. input pressure [bar] | 16 |
| Max. medium temperature [°C] | 60 |
| Min. control range [bar] | 0.5 |
| Page No. | HK132 |
| Pressure gauge display max. [bar] | 16 |
| Pressure gauge display min. [bar] | 0 |
| Pressure gauge Ø [mm] | 63 |
| Sealant | NBR |
| Series | Standard |
| Sight dome | PA |
| Size | 4 |
| Thread | G 1 1/2 |