




### 3/2-5/2-way valve, NAMUR, G 1/4 (1), G 1/4 (3 + 5), 24 V DC

Product is not available anymore, New product: RIEGLER::552.02 3/2-5/2-way valve NAMUR, Alu, Temp. -5 °C to 50 °C, Working pressure 1.5 - 8 bar, Connection G 1/4 (1), G 1/4 (3 + 5), 24 V DC. Pilot-operated 3/2 and 5/2-way spool valves with threaded ports and a NAMUR style interface. Combines high-quality design with a low price. By adding the conversion plate supplied with each valve, the device can be adapted to a 3/2-way function. The valve is turned on by a continuous signal. Turning off causes the piston to be returned to its initial position under pressure. Includes a manual operator as standard.



4047322268837

Article number	<b>103650</b>
Type number	<b>552.02V1</b>
Your price:	<b>35,28 € / Stk</b>

#### Scale of prices:

amount	Price	Unit
1	35,28 €	1 Stk

#### Productdata

Date:	<b>23/09/2019</b>
Price Unit:	1
Quantity Unit:	Stk
Content:	1 Stk
Quantity min:	1
DN	8
Electrical connection	Connector socket PG 9 with LED display
Flow rate [l/min]	1370
Housing	Aluminium
Manual control	latching/non-latching
Max. operating temperature [°C]	50
Max. working pressure [bar]	8
Medium	Air, neutral gases (filtered)
Min. operating temperature [°C]	-5
Min. working pressure [bar]	1.5

Page No.	Web-Only
Port 1	G 1/4
Port 3	G 1/4
Port 5	G 1/4
Sealant	NBR
Voltage	24 V DC