

Straight screw-in fitting, G 1/2 o., for hose 9/12 mm, AF 27, PA

Straight screw-in fitting, G 1/2 o., for hose 9/12 mm, AF 27, Working pressure max. 10 bar (20°C)/max. 1 bar (60°C), PA. Manufactured from high impact-resistant, UV-stabilised engineering plastic, extremely resistant to weathering.Good chemical resistance to benzine, diesel oil, fuel oil and alkalis. Not suitable for use with acids.

4047322021951

Article number	**110778**
Type number	**120.34**
Your price:	**8,17 € / 1 Stk**

Productdata

Date:	**14/05/2018**
Price Unit:	1
Quantity Unit:	Stk
Sales Unit:	1
Quantity min:	1
Clamping ring	Polypropylene (PP)
For hose	9/12 mm
Knurled nut	Polypropylene (PP)
L1	54 mm
L2	14 mm
Max. Operating pressure at 20 °C	10 bar
Max. Operating pressure at 60 °C	1 bar
Page No.	HK514
Screw fitting body	Polyamide (PA)
Thread	G 1/2
a/f	27 mm

Telephone: +49 (0) 7125 94 97-0
Email : info@riegler.de

Subject technical changes

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach