



GruloLine

GruloJet 200

PU sewer cleaning hose, 200 bar

GruloJet 200 is a sewer jetting hose with its pressure carrier, consisting of double-braided highly tearproof synthetic fibres and an extremely abrasion- and cut resistant polyurethane cover. With its working pressure of 200 bar the *GruloJet 200* is eminently suitable for use on sewer cleaning vehicles.

Due to its extremely smooth thermoplastic lining the *GruloJet 200* shows an inferior pressure drop than customary rubber sewer cleaning hoses. Furthermore the lower weight gives you the possibility to increase your vehicle payload.

All hoses are assembled with BSP female/male and ferrules. Delivery takes place with test certificate on each assembled hose.

Technical characteristics

Temperature range: -40 °C to +55 °C

Standard Length: 120 m, 160 m, 180 m, 200 m, 240 m | further lengths on request

Availability: DN 25 up to 350 m, DN 32 up to 250 m, DN 38 up to 200 m



Colour: Light green

Construction

Cover: Polyurethane, cut- and abrasion resistant

Reinforcement: Highly tear-resistant synthetic fibres

Lining: Thermoplastic elastomer

Marking: -  - *GruloJet 200* -  - DN [...] | WP [...] bar | BP [...] bar

Inner-Ø mm	Inner-Ø Inch	Wall thickness mm	WP bar	BP bar	Bending radius mm	Weight/m kg	Article no.
13	1/2	4,70	275	690	75	0,277	10063-013
16	5/8	5,25	220	550	100	0,372	10063-016
19	3/4	5,30	200	500	120	0,431	10063-019
25	1	5,85	200	500	150	0,550	10063-025
32	1 1/4	7,00	200	500	235	0,848	10063-032
38	1 1/2	8,00	200	500	375	1,211	10063-038

Reliable, for sure!