

Digital snap on display, 4-digit LCD display of -1999 to +9999

Digital snap on display for pressure transducer, 4-digit LCD display of -1999 to +9999, Operating temp. 0 °C to +50 °C. The digital plug-in display is freely programmable and easily mounted, and can therefore be retrofitted in a very short time without any problems, even if the transmitter is already in use. No external power supply is required. Suitable for all 4 to 20 mA transmitters with a right-angle connector. Freely programmable by means of keys inside the display.

4047322122566

Article number	**102756**
Type number	**894.20**
Your price:	**226,57 € / Stk**

Scale of prices:

amount	Price	Unit
1	226,57 €	1 Stk

Productdata

Date:	**23/09/2019**
Price Unit:	1
Quantity Unit:	Stk
Content:	1 Stk
Quantity min:	1
Accuracy	± 0.2% ± 1 digit of span
Display	4-digit, 7-segment LCD display, digits 10 mm high
Electrical connection	Adapter for plug acc. to DIN EN 175301-803 A
Height [mm]	35.5
Input signal	4 to 20 mA, 2-wire
Length [mm]	48.5
Max. operating temperature [°C]	50
Measuring range	-1999 to +9999 digits (min. and max. values freely scalable)
Min. operating temperature [°C]	0
Page No.	HK236

Telephone: +49 7125 9497-8320
Email : info@riegler.de

Subject technical changes

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach

Power supply	From 4 to 20 mA loop of transmitter
Protection IP	IP 65
Width [mm]	48.5