



GruloLine

GruloJet 250

PU sewer jetting hose, 250 bar

GruloJet 250 is a thermoplastic sewer cleaning hose that has been developed especially for the equipment of professional sewer cleaning vehicles. The pressure carrier, consisting of double-braided highly tearproof aramid- and synthetic fibres, guarantees long endurance and therefore decreases your expenses. The *GruloJet 250* is floatable and extremely abrasion- and cut resistant. Furthermore it stands out due to its excellent flexibility, which simplifies its handling and your daily work. Being one third lighter than common rubber sewer cleaning hoses, it enables you to increase your vehicle payload.

All hoses are assembled with BSP female/male and ferrules. Delivery takes place with test certificate on each assembled hose.

Technical characteristics

Temperature range: -40 °C to +55 °C

Standard Length: 80 m, 120 m, 160 m, 180 m, 200 m, 240 m | further lengths on request

Availability: DN 25 up to 350 m, DN 32 up to 250 m, DN 38 up to 150 m

Colour: Red


Construction

Cover: Polyurethane, cut- and abrasion resistant

Reinforcement: Highly tear-resistant aramid- and synthetic fibres

Lining: Thermoplastic elastomer

Marking: - - GruloJet 250 - - DN [...] | WP 250 bar | BP 625 bar | [Datum]



Inner-Ø mm	Inner-Ø Inch	Wall thickness mm	WP bar	BP bar	Bending radius mm	Weight/m kg	Article no.
19	3/4	5,30	250	625	100	0,406	10089-019
25	1	5,85	250	625	150	0,643	10089-025
32	1 1/4	7,00	250	625	235	0,985	10089-032
38*	1 1/2	7,00	250	625	300	1,150	10089-038

* on request

Reliable, for sure!