



Plug nipple without pressure eliminator, Series B, G 1 IT

Plug nipple without pressure eliminator, Series B, hardened, galvanised steel, G 1 IT, I.D. 20, Operating pressure max. 300 bar. Acc. to ISO 7241-1, B Series. This coupling series combines an extremely small pressure drop with maximum hydraulic power transmission. Interchangeable with all couplings and plugs manufactured according to the above standard. The patented pressure eliminator permits disconnection even if back pressure has built up (up to 200 bar). The pressure eliminator can be used in all applications where there is a risk of pressure build-up after the line has been separated. It allows effortless connection under pressure. The mating part must be pressureless in order for the eliminator to function optimally. Areas of application: chemical industry, food technology, automotive, offshore.



4047322057028

Article number	107737
Type number	242.55 B
Your price:	43,02 € / 1 Stk

Productdata

Date:	14/05/2018
Price Unit:	1
Quantity Unit:	Stk
Sales Unit:	1
Quantity min:	1
Ball	Stainless steel
Connection	G 1 IT
DN	20
Length	70 mm
Max. operating temperature	100 °C
Min. operating temperature	-30 °C
Operating pressure max.	300 bar
Page No.	HK403
Push-in plug	Steel
Sealant	NBR
Spring	Stainless steel
Valve	Brass

a/f

42 mm