

Tempered coupling DN 6, Exterior thread, Brass, G 1/4 90°

Tempered coupling DN 6, Exterior thread, Brass 2.0401, G 1/4 90°, Operating pressure max. 15 bar, Temp. -20 °C to 160 °C. Compatible with HASCO Z 8 system.For temperature control applications involving hot or cold water or heat transfer oil, e.g. for cooling circuits on plastics processing machines.Optionally with free passage, one or both sides sealing.Female-threaded couplings and plugs with female-threaded PTFE seal.

4047322258142

Article number	**107928**
Type number	**270.36**
Your price:	**15,52 € / 1 Stk**

Productdata

Date:	**14/05/2018**
Price Unit:	1
Quantity Unit:	Stk
Sales Unit:	1
Quantity min:	1
Ball	Stainless steel
Connecting thread	G 1/4 90°
Length	47 mm
Material	Brass 2.0401
Max. ambient temperature	160 °C
Max. medium temperature	160 °C
Max. operating pressure	15 bar
Medium	Air, water, oil, vacuum
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK412
Retaining ring	Stainless steel
Sealant	FPM (PTFE coated)
Spring	Stainless steel

a/f	17 mm