



GrüloLine

DN 38
ALSO IN
WP 200 BAR

GrüloKan 250

Rubber sewer cleaning hose

GrüloKan 250 offers you all benefits of a professional rubber sewer cleaning hose. The specially developed rubber compound guarantees a long operating life, high abrasion resistance and an extreme flexibility. **GrüloKan 250** is characterized by its easy handling, light weight and excellent pressure resistance. In addition **GrüloKan 250** has a very small bending radius. The hose cover is resistant to abrasion and cut exposure, aging and water resistant.

All hoses are assembled with BSP female/male and ferrules. Delivery takes place with test certificate on each assembled hose.

Technical characteristics

Temperature range: -40 °C to +70 °C

Standard Length: 60 m, 80 m, 120 m, 160 m, 180 m, 200 m, 220 m, 240 m
further lengths on request

Availability: 10 m up to 240 m | from DN 32 up to 200 m

Colour: Black

Construction

Cover: NR/SBR, highly abrasion resistant, smooth

Reinforcement: Twofold braided synthetic fibres

Lining: NR/SBR, black, smooth

Transfer tape: G+L Ellipse GrüloKan 250 bar DN [..]

| Inner-Ø mm | Inner-Ø Inch | Wall thickness mm | WP bar | BP bar | Bending radius mm | Weight/m kg | Article no. |
|---------------|-----------------|----------------------|-----------|-----------|----------------------|----------------|-------------|
| 13 | 1/2 | 6,00 | 250 | 625 | 70 | 0,450 | 10066-013 |
| 16 | 5/8 | 6,00 | 250 | 625 | 80 | 0,530 | 10066-016 |
| 19 | 3/4 | 6,00 | 250 | 625 | 90 | 0,600 | 10066-019 |
| 25 | 1 | 7,00 | 250 | 625 | 105 | 0,810 | 10066-025 |
| 32 | 1 1/4 | 7,50 | 250 | 625 | 140 | 1,080 | 10066-032 |
| 38 | 1 1/2 | 8,00 | 250 | 625 | 160 | 1,250 | 10066-038 |

Reliable, for sure!