




Quick-connect coupling I.D. 5, bright brass, Sleeve I.D. 9, M12x1

Quick-connect coupling I.D. 5, bright brass, Sleeve I.D. 9, Bulkhead thr. M12x1, Operating pressure 0-35 bar, Temp. -20°C to 100°C. One-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. Areas of application: Pneumatic system, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology.



4047322285377

Article number	107140
Type number	243.34
Your price:	11,69 € / 1 Stk

Productdata

Date:	14/05/2018
Price Unit:	1
Quantity Unit:	Stk
Sales Unit:	1
Quantity min:	1
Ball	Stainless steel
Bulkhead fitting	M12x1
Connection	Stem, I.D. 9
DN	5
Flow rate	560 l/min (air)
Flow rate measurement	at 6 bar and $\Delta p = 0.5$ bar
Housing	Brass with a bare metal surface
Length	60 mm
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C

Operating pressure	0 to 35 bar, maximum static working pressure (non-pulsating)
Page No.	HK366
Retaining ring	Stainless steel
Sealant	NBR
Sleeve	Brass with a bare metal surface
Spring	Stainless steel
Valve body	Brass with a bare metal surface
a/f	17 mm