

Round cylinder »MI« double-acting, Piston Ø 25, Stroke 600, G 1/8

Round cylinder »MI« ISO 6432, double-acting, Piston Ø 25, Stroke 600, G 1/8, Working pressure 1 - 10 bar, Temp. -20 °C to 70 °C. Suitable for filtered, unlubricated or lubricated compressed air.If lubrication is used, it must be continuous.»CA« type = bottom cover with male thread – hinge model

4047322314725

Article number	**114880**
Type number	**11.DM.25600**
Your price:	**79,50 € / 1 Stk**

Productdata

Date:	**15/05/2018**
Price Unit:	1
Quantity Unit:	Stk
Sales Unit:	1
Quantity min:	1
Connection	G 1/8
Jacket	Stainless steel 1.4301
Max. temperature range	70 °C
Max. working pressure	10 bar
Min. temperature range	-20 °C
Min. working pressure	1 bar
Piston	Aluminium
Piston rod	Stainless steel 1.4301
Piston rod ET	M10x1.25
Piston rod-Ø	10 mm
Piston Ø	25 mm
Sealant	NBR
Stroke	600 mm
Version	»CA« type, acc. to ISO 6432

Telephone: +49 (0) 7125 94 97-0
Email : info@riegler.de

Subject technical changes

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach