

3/2-way valve, NAMUR, monostable, NC, G 1/4, 24 V DC

3/2-way valve, NAMUR, NC, Anodised aluminium, Operating temp. max. 70°C, Working pressure 1.5-10 bar, Connection G 1/4, 24 V DC. 3/2 and 5/2-way spool valves, monostable, with air purging function and pneumatic spring return. With latching manual operator and optional outgoing air restriction.

4047322272438

Article number	**103658**
Type number	**551.12**
Your price:	**42,52 € / Stk**

Scale of prices:

amount	Price	Unit
1	42,52 €	1 Stk

Productdata

Date:	**23/09/2019**
Price Unit:	1
Quantity Unit:	Stk
Content:	1 Stk
Quantity min:	1
Connection	G 1/4
DN	7
Electrical connection	Connector socket Pg 9
Flow rate [l/min]	1250
Housing	Aluminium anodised
Manual control	latching
Max. operating temperature [°C]	70
Max. working pressure [bar]	10
Medium	Air, neutral gases (filtered)
Min. operating temperature [°C]	-20
Min. working pressure [bar]	1.5
Page No.	HK311

Telephone: +49 7125 9497-8320
Email : info@riegler.de

Subject technical changes

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach

Power input	3 W=/ 5 VA~
Scope of delivery	Plug connector PG 9, 1 coding pin, 2 Orings, 2 fixing screws
Sealant	NBR
Spool	Stainless steel
Voltage	24 V DC