




### Plug nipple without pressure eliminator, Series A, I.D. 13

Plug nipple without pressure eliminator, Series A, I.D. 13, hardened, galvanised steel, G 1/2 IT, PN max. 250 bar. Acc. to ISO 7241-1, A Series. This coupling series combines an extremely small pressure drop with maximum hydraulic power transmission. Interchangeable with all couplings and plugs manufactured according to the above standard. The patented pressure eliminator permits disconnection even if back pressure has built up (up to 200 bar). The pressure eliminator can be used in all applications where there is a risk of pressure build-up after the line has been separated. It allows effortless connection under pressure. The mating part must be pressureless in order for the eliminator to function optimally. Areas of application: Agricultural machines, construction machines, municipal engineering, transportation engineering, industrial plant.



4047322056939

Article number	<b>107724</b>
Type number	<b>242.51 A</b>
Your price:	<b>13,30 € / Stk</b>

#### Scale of prices:

amount	Price	Unit
1	13,30 €	1 Stk

### Productdata

Date:	<b>23/09/2019</b>
Price Unit:	1
Quantity Unit:	Stk
Content:	1 Stk
Quantity min:	1
Ball	Stainless steel
Connection	G 1/2 IT
Housing	Brass
Length [mm]	41
Max. operating pressure [bar]	250
Max. operating temperature [°C]	100
Min. operating temperature [°C]	-30

Page No.	HK605
Sealant	NBR
Spring	Stainless steel
Unlocking sleeve	Nickel-plated brass
Valve	Hard drawn brass
a/f [mm]	27