

Service unit 3-part »variobloc« with PC container, Size 2, G 1

Service unit 3-part »variobloc« with PC container, Size 2, G 1, Input pressure max. 16 bar, Medium / ambient temp. max. 50 °C. Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator. Approved series in modern industrial design, with the following key benefits: - Simple handling - Convenient modular assembly thanks to innovative fasteners - Excellent flow values

4047322212755

Article number	**100716**
Type number	**VW 16**
Your price:	**228,20 € / Stk**

Scale of prices:

amount	Price	Unit
1	228,20 €	1 Stk

Productdata

Date:	**23/09/2019**
Price Unit:	1
Quantity Unit:	Stk
Content:	1 Stk
Quantity min:	1
A [mm]	264
B [mm]	274
Bowl	Polycarbonate container
C [mm]	98
Condensate drain	Manual
Diaphragms	NBR
Filter rating [µm]	40
Flow rate [l/min]	5000
Flow rate measurement	At P₁ = 10 bar, P₂= 6 bar and pressure drop Δ_p = 1 bar
Housing	Die-cast zinc

Max. ambient temperature [°C]	50
Max. control range [bar]	10
Max. input pressure [bar]	16
Max. medium temperature [°C]	50
Min. control range [bar]	0.5
Page No.	HK110
Pressure gauge display max. [bar]	10
Pressure gauge display min. [bar]	0
Sealant	NBR
Series	variobloc
Sight dome	PA
Size	2
Spring bonnet	POM
Thread	G 1

Telephone: +49 7125 9497-8320
Email : info@riegler.de

Subject technical changes

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach