

Round cylinder TP double-acting, Piston Ø 25, Stroke 500, G 1/8

Round cylinder TP (ISO 6432) double-acting, Piston Ø 25, Stroke 500, G 1/8, Working pressure max. 10 bar, Temp. -10 °C to 60 °C. Inexpensive standard version with aluminum pipe and magnet piston. Suitable for filtered (50 µm), unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.

4047322288644

Article number	**105729**
Type number	**8.DM.25500**
Your price:	**52,57 € / Stk**

Scale of prices:

amount	Price	Unit
1	52,57 €	1 Stk

Productdata

Date:	**23/09/2019**
Price Unit:	1
Quantity Unit:	Stk
Content:	1 Stk
Quantity min:	1
Bottom	Technopolymer
Bushing	Technopolymer
Cap	Technopolymer
Connection	G 1/8
Design	Connection: Aluminium pipe / end caps flanged
Jacket	Aluminium alloy, anodised
Max. temperature range [°C]	60
Max. working pressure [bar]	10
Min. set pressure [bar]	0.6
Min. temperature range [°C]	-10
Page No.	HK389
Piston gasket	PU

Piston rod	C45 steel, hard chrome-plated
Piston rod ET	M10x1.25
Piston rod gasket	PU
Piston Ø [mm]	25
Stroke [mm]	500

Telephone: +49 7125 9497-8320
Email : info@riegler.de

Subject technical changes

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach