

Camera Unit CCD – 107 Colour

free view into enclosed areas

- small, compact and robust camera
- nitrogen filled, shock proof and with heated lens
- range of use from -40° to $+70^{\circ}\text{C}$
- large 7" flat screen
- high resolution, anti-glare and with day and night switchover
- easy to use
- excellent picture quality



Free view

In enclosed or badly visible areas makes work with a fork lift easier. With a camera on the fork lift truck it is easier to recognise a dangerous situation early and to react in time. The truck is driven easier and safer, accidents are reduced, down-time and repair costs are reduced. Material flow is altogether faster and more constant.

Camera CCC – 102

Is small, robust, shock-proof and can be installed in almost any position on the fork lift truck.

By means of a holder that can move in any direction, it can reach the area

required. An angle of spread of 102° (wider angle of spread up to 145° is available) corresponds to the human eye and corresponds to human estimation of distances and size. Due to the nitrogen filled housing and heated lens, the camera is shock-proof and can also be used in poor weather conditions.

The high light sensitivity of the camera also offers a **clear picture on the monitor** at only 0.5 Lux.

The LCD-/TFT Monitor is also swing-fitted so that the driver can position the monitor in his desired

direction of view and set it to his height.

The polaroid coated screen darkens the picture automatically in the case of high sun conditions so that an optimum image reproduction is assured.

With 430.000 Pixels, the 7" screen delivers a sharply contoured picture.

When using several cameras, the picture on the monitor is always switched on to the direction of travel.

