

Compressed air distributor »Multi-Link«, 5 standard couplings 7.6

Product is not available anymore, New product: RIEGLER::VTM-5KS Compressed air distributor »Multi-Link«, with standard coupling I.D. 7.6, Removal unit 5, Operating pressure max. 16 bar. Modular distributor system for flexible workplace design, can be rotated 180°. Equipped for 2 to 5 bleed units, optionally with: - G 1/2 female threaded connection for individually adaption output segments - DN 7.6 quick disconnect safety couplings

4047322350617

Article number	**107397**
Type number	**VTM-5K**
Your price:	**209,91 € / Stk**

Scale of prices:

amount	Price	Unit
1	209,91 €	1 Stk

Productdata

Date:	**23/09/2019**
Price Unit:	1
Quantity Unit:	Stk
Content:	1 Stk
Quantity min:	1
Bleed units	5
Connecting thread	G 1/2 female
Connection	Standard couplings DN 7.6
Material	Galvanised steel / brass
Max. operating pressure [bar]	16
Max. temperature range [°C]	100
Medium	Compressed air, non-corrosive gases
Min. temperature range [°C]	-20
Page No.	WEB
Sealant	NBR

Telephone: +49 7125 9497-8320
Email : info@riegler.de

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach

Subject technical changes