



Condensate drain line »drukodrain«, Pulse controlled, 230 V/50 Hz

Condensate drain line »drukodrain«, Pulse controlled, Voltage 230 V / 50 Hz, Operating pressure max. 16 bar. Ruggedly designed, cycle-controlled drain system for controlled drainage of compressed air condensate, proven thousands of times over and ready to use immediately. In contrast with conventional clock generators, the blowing and pause times of the »drukodrain« are not set in seconds or minutes but in bar or m³/min, depending on the pneumatic system installed upstream. Efficient and reliable operation is assured. Benefits of »drukodrain«: - Clock generator settings according to compressed air system: "bar" - for operating pressure "m³/min" - for compressor or dryer capacity - Suitable for compressor / dryer capacities up to 20 m³/min - Integrated dirt pan and G 1/2 ball valve - 2 m connection cable with plug (230 V / 50 Hz) included



4047322205184

Article number	101623
Type number	KA 10
Your price:	114,76 € / Stk

Scale of prices:

amount	Price	Unit
1	114,76 €	1 Stk

Productdata

Date:	23/09/2019
Price Unit:	1
Quantity Unit:	Stk
Content:	1 Stk
Quantity min:	1
Max. operating pressure [bar]	16
Page No.	HK182
Protection IP	IP 65
Voltage	230 V / 50 Hz