




Quick relief valve »lineonline«, with silencer, for hose Ø 8 mm

Quick relief valve »lineonline«, with silencer, Hose - hose, for hose Ø 8 mm, Operating pressure 1 - 10 bar. A carefully selected assortment of products for installation in pneumatic circuits. These small, highly efficient components allow all pneumatic functions to be implemented anywhere in the circuit. The series has an ultramodular design. All components can be installed in parallel in series in a mixed parallel / serial configuration. Available as Pipe / pipe connection with two plug connectors Thread / pipe connection with one plug connector and one nickel-plated brass thread. Installation: Wall mounting (housing with drilled holes) Bracket mounting (mounting bracket available as an accessory) Panel mounting (with bracket or lock nut) Exhaust can be silenced by a stainless steel silencer or conveyed using a push-in fitting with an air exhaust device.



4047322086981

Article number	106768
Type number	431-8
Your price:	11,69 € / 1 Stk

Productdata

Date:	14/05/2018
Price Unit:	1
Quantity Unit:	Stk
Sales Unit:	1
Quantity min:	1
A	57.2 mm
B	31.5 mm
Body	Technopolymer
Exhaust flow rate at 6.3 bar	1000 NI/min
Flow rate at 6.3 bar	400 NI/min
For pipe Ø	8 mm
I	18.7 mm
Internal parts	Nickel-plated brass, brass, technopolymer, stainless steel
Max. operating pressure	10 bar
Max. temperature range	60 °C

Min. operating pressure	1 bar
Min. temperature range	-20 °C
Page No.	HK337
Pneumatic symbols	On housing
Sealant	NBR