

Glycerine pressure gauge »pressure line« G 1/4, 0-600bar/8500 psi

Glycerine press. gauge »pressure line« Connection, rear, centric, G 1/4, Goods class 1.6, Measurement range 0-600bar/8500 psi, Ø63. Low-priced series of high-quality, glycerine-filled pressure gauges with stainless steel housing for all applications involving measurements in areas with high dynamic pressure loads and vibration levels.Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

4047322177252

Article number	**116337**
Type number	**816-CDE**
Your price:	**20,35 € / 1 Stk**

Productdata

Date:	**15/05/2018**
Price Unit:	1
Quantity Unit:	Stk
Sales Unit:	1
Quantity min:	1
Accuracy class	1.6
Connection	G 1/4
Connection position	rear, centrical
Diameter	63 mm
Front glass	Glass
Housing	Stainless steel
Max. ambient temperature	60 °C
Max. medium temperature	60 °C
Measuring element	Brass
Measuring range max. bar	600
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Movement	Brass
Scale graduation in the bar area	20 bar

Telephone: +49 (0) 7125 94 97-0
Email : info@riegler.de

Subject technical changes

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach

Telephone: +49 (0) 7125 94 97-0
Email : info@riegler.de

Subject technical changes

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach