

Compact pressure regulator, Push-in connector for hose 10, G 1/4

Compact pressure regulator, Push-in connector for hose 10, G 1/4, Control range 0 - 8 bar, Temp. 0°C to 70°C, nickel-plated brass. Piston pressure regulator with self-relieving design, hollow bolt and pivoting ring piece. The regulator is screwed directly into the consumer (e.g. cylinder, handling equipment, etc.). The working pressure can thus be adapted to the specific application.

4047322181648

Article number	**107050**
Type number	**3621.014-10**
Your price:	**25,89 € / 1 Stk**

Productdata

Date:	**14/05/2018**
Price Unit:	1
Quantity Unit:	Stk
Sales Unit:	1
Quantity min:	1
Adjusting screw	Nickel-plated brass
B	63 mm
C	26.5 mm
Captive seals	Polyamide (glass fibre-reinforced)
For hose	10 mm
Hollow bolt	Nickel-plated brass
Internal parts	Brass with a bare metal surface
Max. control range	8 bar
Max. input pressure	10 bar
Max. temperature range	70 °C
Min. control range	0 bar
Min. temperature range	0 °C
Page No.	HK351
Pivoting arm	Nickel-plated brass

Telephone: +49 (0) 7125 94 97-0
Email : info@riegler.de

Subject technical changes

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach

Sealant	NBR
Thread	G 1/4
a/f	17 mm