

Filter »variobloc« with PC container, Size 2, G 1

Filter »variobloc«, PC container, Size 2, G 1, Input pressure max. 16 bar, Med. / ambient temp. max. 50 °C, Manual bleeder valve. Centrifugal separators with a sintered filter element.Filtration takes place in a 2-stage process comprising cyclone separation (condensate) and a PE filter element (particles).Approved series in modern industrial design, with the following key benefits:- Simple handling- Convenient modular assembly thanks to innovative fasteners- Excellent flow values

4047322212694

Article number	**100682**
Type number	**VF 26**
Your price:	**82,06 € / 1 Stk**

Productdata

Date:	**14/05/2018**
Price Unit:	1
Quantity Unit:	Stk
Sales Unit:	1
Quantity min:	1
A	124 mm
B	202 mm
Bowl	Polycarbonate container
C	26 mm
Condensate drain	Manual
Filter rating	40 µm
Flow rate	3500 l/min
Flow rate measurement	At P1 = 6 bar and pressure drop Δp = 1 bar
Housing	Die-cast zinc
Max. ambient temperature	50 °C
Max. input pressure	16 bar
Max. medium temperature	50 °C
Page No.	HK066
Sealant	NBR

Telephone: +49 (0) 7125 94 97-0
Email : info@riegler.de

Subject technical changes

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach

Series	variobloc
Size	2
Thread	G 1