

Round cylinder, single-acting, Piston Ø 25, Stroke 50, G 1/8

Round cylinder, ISO 6432, single-acting, Magnet, Piston Ø 25, Stroke 50, G 1/8, Working pressure max. 10 bar, Temp. -10°C to 80°C. Single and double-acting cylinders, with magnetic piston.Suitable for filtered, unlubricated or lubricated compressed air.If lubrication is used, it must be continuous.

4047322011044

Article number	**105839**
Type number	**1.EM.25050**
Your price:	**51,37 € / 1 Stk**

Productdata

Date:	**15/05/2018**
Price Unit:	1
Quantity Unit:	Stk
Sales Unit:	1
Quantity min:	1
Connection	G 1/8
Design	Flanged joint between stainless steel barrel and heads
Jacket	Stainless steel 1.4301
Max. temperature range	80 °C
Max. working pressure	10 bar
Min. set pressure	0.6 bar
Min. temperature range	-10 °C
Page No.	HK286
Piston	Synthetic (acetal) resin
Piston rod	C45 steel, hard chrome-plated
Piston rod thread	M10x1.25
Piston Ø	25 mm
Sealant	NBR
Stroke	50 mm

Telephone: +49 (0) 7125 94 97-0
Email : info@riegler.de

Subject technical changes

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach