



Automation & Robotics

# FOCOVISION™ SPF-3

## FOCOVISION™ SPF-3: Prescription Version with frame positioning assistance.

The Focovision™ by Transmission SPF-3 is used in optical laboratories where the lenses are mounted into frames. It is connected to the computer network, from which it receives the nominal values of the prescription lens. Its main advantages are repeatability, accuracy, and easy calibration. It performs a lens optical power measurement compliant with ISO/ANSI standards by using a light beam according to 'IOA' (Infinity On Axis) configuration at a certain wavelength (546 nm or 587 nm) and by measuring in all directions (360 degrees - «ring method»). In addition, it's equipped with a frame positioning device and has a user friendly interface; permitting an operator to learn how to perform the complete lens control of the mounted lenses with little training required.



# Main Features



The FOCOVISION™ by transmission SPF-3 is used in optical laboratories to inspect lenses that have been mounted in the frame.

**Powerful interface capabilities-**  
When interfaced to the host computer, data specific to the job as well as the instructions to the operator for the product type being processed can be transmitted from the host computer through the FOCOVISION™ server via barcode scan.

Information for the job and the specific customer requirements can be accessed. A "go or no-go" message can be provided to the operator on the instrument's screen avoiding errors due to subjective interpretation.

Messages specific to the job can also be transmitted to the operator via the instrument's screen providing the operator with important instructions.

**Low Maintenance:**  
The measurement device has no moving parts. The only replacement parts are the air and dust filter. New light source, based on the long-life LED technology, with easy plug and play replacement. Calibration of the instrument is easy and automatic requiring no mechanical adjustment. The frame holder attached to the instrument is robustly constructed to industrial use standards and is easy to use.

**Type : SPF-3**

# Technical Specifications



**Accurate and consistent:**  
The FOCOVISION™ uses the "ring method". It measures the optical lens power by transmitting a light beam, in all directions (360 degrees) through the lens with the appropriate wavelength (e-line or d-line, in accordance with the ANSI/ISO Standards).

It accurately measures optical power to 0.02D and prism power to 0.02 cm/m, +1%.

**Range:**  
The operating range of the instrument exceeds the normal requirements of the lab.  
Optical power in the main axis: -20D to +20D  
Prism power: 0 to 5 cm/m (S= -14D increasing with S)

**Powerful Data analysis-**  
The actual parameters of the measured lens can be transmitted back to the host computer via the FOCOVISION™ server. This information can be stored as part of the record for the job for reference at a later date.  
The data can also be used in a production control analysis to assist the lab management in improving the production process.

The FOCOVISION™ server can also provide a data download of the records of measured work to a secondary software analysis system if the customer prefers that method of production process control.

**Included :**  
- Printer to provide a ticket with measured information  
- Visualisation system for the positioning of bifocal and progressive lenses.

# Benefits



**Positioning assistance:**  
The FOCOVISION™ display provides assistance to the operator to help them position the frame and lens to be measured properly, creating a user friendly and fast process. The positioning target, displayed at every step of the procedure, and operator instructions projected on the monitor are easy to see and understand.


Each lens position, within the frame (correct mounting) is checked in accordance with the micro-engravings of the progressive or the segment for bifocal lens which reduces subjective interpretation of the measurements and verifies proper lens mounting.

For single vision jobs, automatic recalculation of measured results (prism, decentration) is possible without tedious positioning by the operator (the operator doesn't need to position at the optical center anymore). Horizontal and vertical imbalance is determined by the software within the FOCOVISION™.

A diagram on the screen displays the difference between the measured values and the target values of the lens parameters for easy and precise understanding by the operator.

A barcode reader, to easily interface the FOCOVISION™ with the host computer, is included.

# Options



- A computer Server (required for first unit) is capable of supporting an indefinite number of FOCOVISION™ instruments
- A vacuum holding system
- A 3 dots marking system

**LATEST DEVELOPMENT:**

- The NEW FOCOVISION SPF-3 software is based on Windows 10 Embedded OS.
- A new light source provides an improved ring image. Effect of local defects (dusts,...) are detected and corrected using a proprietary technology. The new light source, based on the long-life LED technology can easily be exchanged (plug and play), leading to better accuracy in lab conditions.

For information purpose only.  
Specifications subject to change without prior notice.  
The sale of all of Automation & Robotics products is subject to the company's applicable Warranty and Limitations of Warranty and to the company's Standard Terms and Conditions of Sale.

Parc industriel de Lambermont  
Rue des Ormes 111  
B-4800 Verviers - Belgium  
Tél.: +32 (0)87 322 323  
Fax: +32 (0)87 310 406  
e-mail: aut-rob@ar.be

T.V.A.: BE 0423.637.107  
R.P.M.: Verviers  
www.ar.be

