

3/2-way solenoid valve »lineonline« silenced venting, Hose Ø8, NO

3/2-way solenoid valve »lineonline« silenced venting, Hose - hose, Hose Ø 8, NO, 24 V DC, Operating pressure 2.5 - 7 bar. Though small in size, these valves are solenoid-piloted and feature very high performance. Each valve comes complete with a monostable manual control and LED. Exhaust can be damped with a silencer or conveyed via a pipe fitting. Function corresponds to the normal position of the valve.

4047322092388

Article number	**106846**
Type number	**481-8**
Your price:	**62,57 € / Stk**

Scale of prices:

amount	Price	Unit
1	62,57 €	1 Stk

Productdata

Date:	**23/09/2019**
Price Unit:	1
Quantity Unit:	Stk
Content:	1 Stk
Quantity min:	1
A [mm]	57.2
B [mm]	63.5
Body	Technopolymer
Flow rate at 6.3 bar and Δp 1.0 bar [Nl/min]	700
For pipe Ø [mm]	8
Function	NO
I [mm]	18.7
Internal parts	Nickel-plated brass, brass, technopolymer, stainless steel
Max. operating pressure [bar]	7
Max. temperature range [°C]	60

Min. operating pressure [bar]	2.5
Min. temperature range [°C]	-20
Operating voltage	24 V DC
Page No.	HK496
Pneumatic symbols	On housing
Power input	1.2 W
Sealant	NBR