

Stainless steel filter regulator, 1.4404, G 1/4, 1 - 15 bar

Stainless steel filter regulator, 1.4404, with secondary venting (reversible), incl. press. gauge, G 1/4, Control range 1 - 15 bar. Stainless steel filter regulators with self-relieving (not for liquid media) containing no non-ferrous metals for use in the food processing, chemical, mining, plant construction and special machinery industries as well as in the medical technology.

4047322101967

Article number	**101207**
Type number	**572.14 D**
Your price:	**675,62 € / 1 Stk**

Productdata

Date:	**14/05/2018**
Price Unit:	1
Quantity Unit:	Stk
Sales Unit:	1
Quantity min:	1
A	65 mm
B	250 mm
C	125 mm
Condensate drain	Manual drain valve
Diaphragms	PTFE on NBR-carrier
Filter rating	50 µm
Flow rate	2500 l/min
Flow rate measurement	At P1 = 10 bar, P2 = 5 bar and pressure drop Δp ≤ 1 bar
Housing	Stainless steel 1.4404 (AISI 316L)
Max. ambient temperature	60 °C
Max. control range	15 bar
Max. input pressure	30 bar
Max. medium temperature	130 °C
Min. control range	1 bar
Page No.	Web-Only
Sealant	FKM

Telephone: +49 (0) 7125 94 97-0
Email : info@riegler.de

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach

Thread	G 1/4

Telephone: +49 (0) 7125 94 97-0
Email : info@riegler.de

Subject technical changes

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach