

Microfilter for high pressures up to 60 bar, 0.01 µm, G 1

Microfilter for high pressures up to 60 bar, manual bleeder valve, 0.01 µm, G 1, Brass container, Operating temp. 0 °C to 90 °C. Fine filter for all applications with particularly strict compressed air purity requirements. Micro-filters should always be used in conjunction with a standard filter connected upstream to trap coarse impurities and protect the micro-filter inserts.

4047322270373

Article number	**101183**
Type number	**680.44**
Your price:	**263,94 € / Stk**

Scale of prices:

amount	Price	Unit
1	263,94 €	1 Stk

Productdata

Date:	**23/09/2019**
Price Unit:	1
Quantity Unit:	Stk
Content:	1 Stk
Quantity min:	1
A [mm]	80
B [mm]	196
Bowl	Brass
C [mm]	29
Efficiency [%]	99.9999
Filter element	Borosilicate
Filter rating [µm]	0.01
Flow rate [l/min]	2300
Flow rate measurement	At P₂ = 6 bar and pressure drop Δ_p = 0.5 bar
Housing	Aluminium
Max. input pressure [bar]	60
Max. operating temperature [°C]	90

Telephone: +49 7125 9497-8320
Email : info@riegler.de

Subject technical changes

RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach

Min. operating temperature [°C]	0
Page No.	HK144
Sealant	NBR
Thread	G 1