



Throttle check valve, Supply air throttle, quick conn. Hose 10/8, G3/8

Throttle check valve, Supply air throttle (»V«) quick connector Hose 10/8, G 3/8 PN max. 10 bar, Temperature 0 °C to 70 °C. For fine regulation of a cylinder piston speed in the forward and return motion and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder to restrict the incoming air. Compact type of construction, also ideal where space is restricted.



4047322181822

Article number	106888
Type number	357.038-10
Your price:	16,89 € / Stk

Scale of prices:

amount	Price	Unit
1	16,89 €	1 Stk

Productdata

Date:	23/09/2019
Price Unit:	1
Quantity Unit:	Stk
Content:	1 Stk
Quantity min:	1
Adjusting screw	Nickel-plated brass
B [mm]	50
C [mm]	30.5
Captive seals	Polyamide (glass fibre-reinforced)
For hose [mm]	10 / 8
Hollow bolt	Nickel-plated brass
Internal parts	Brass with a bare metal surface
Max. operating pressure [bar]	10
Max. temperature range [°C]	70
Min. temperature range [°C]	0
Page No.	HK498

Pivoting arm	Nickel-plated brass
Sealant	NBR
Thread	G 3/8
a/f [mm]	20